

PRODUCT SPECIFICATION

Floor type			rigid vinyl flooring with click system			
Collection			Wood	Herringbone	Wood+	Herringbone+
Format			plank	herringbone	plank	herringbone
Overall thickness		ISO 24337	5 mm		6 mm	
Wear layer		EN 429	0,30 mm		0,55 mm	
Plank/tile size		ISO 24337	180 x 1220 mm	125 x 625 mm	180 x 1220 mm	125 x 625 mm
Total weight		ISO 23997	8400 g/m2	8200 g/m2	9500 g/m2	9200 g/m2
Construction						
composite base made from stone and polymers						
Surface			regular wood embossed	light wood embossed	regular wood embossed	light wood embossed
Finish						
polyurethane matt coating						
Underlay						
pre-attached IXPE						
Installation						
floating (click system under license from Unilin)						
Warranty			20 years residential 10 years commercial		25 years residential 10 years commercial	
Pieces per box			10 pcs	12 pcs	10 pcs	16 pcs
Area per box			2,2 m2	0,94 m2	2,2 m2	1,25 m2
Weight per box			18,5 kg	7,75 kg	21 kg	11,5 kg
Fire resistance		EN 13501-1	Bfl-s1			
Formaldehyde emission		EN 14041	E1			
Slip resistance		EN 13893 DIN 51130:2014	DS R10			
Dimension stability		EN 23999	norm: ≤ 0,25% ≤ 0,15%			
Curling		EN 23999	pass (≤ 2mm)			
Wear group classification		EN ISO 10874	23: domestic heavy 31: commercial moderate		23: domestic heavy 33: commercial heavy	
Abrasion resistance		EN13329 Annex E	pass (≥ 1600 cycles)		pass (≥ 4000 cycles)	
Castor chair		EN 425	pass (no visible change)			
Residual indentation		EN 434	pass (≤ 0,1 mm)			
Stain resistance		EN 438	pass (class 5)			
UV resistance		ISO 105-B02	pass (≥ 6)			
Thermal conductivity		EN 12667	0,096 W/mK (floor + underlay)		0,109 W/mK (floor + underlay)	
Thermal resistance		EN 12667	0,052 (m2K)/W (floor + underlay)		0,055 (m2K)/W (floor + underlay)	
Underfloor heating						
suitable for underfloor heating under certain conditions						
Acoustic insulation		EN ISO 717-2	ΔLw 19 dB			

Multi-layer rigid vinyl flooring under VinCore brand come with the warranty. More details about the conditions can be found in the relevant warranty documents.
Created based on declaration of performance DOP-2022/01 v. EN02.



EPUFLOORING Sp. z o.o.
Office: Kopcinskiego 77, 90-033 Lodz, Poland
Warehouse: Ossendowskiego 3B, 93-228 Lodz, Poland
dok.epuflooring@epufloor.com
www.vincore.pl